



## EC-type examination certificate

Registration number / Reference mark C3435NOIR

The company

**NoIR Laser Company, LLC**

6155 Pontiac Trail  
SOUTH LYON MI 48178

Applicant's code NOIR

hereby receives the confirmation that the product/s

**laser protection filter**

of the type

**DI4 / DI4.4 and 8 base**

conforms to

**Rules 89/686/EWG  
DIN EN 207:2002-12**

Test report(s): 77550-PTB-03, 114311-PZA-05, 1030-PZA-07


**Identification Information see annex**

See annex for further information.

DIN CERTCO GmbH  
Prüf- und Zertifizierungszentrum Aalen  
Gartenstraße 133, 73430 Aalen Germany



2007-04-24

  
Dipl.-Ing. (FH) Stefan Merkel  
Notified Body 0196

## Annex

to the Certificate with Registration No. C3435NOIR, dated 2007-04-24

Herewith, DIN CERTCO PZA certifies that the model is in compliance with the basic requirements of the Directive 89/686/EEG for personal protective equipment. The certificate is based both / either on the tests and / or on the technical documentation submitted by the manufacturer.

### Test report(s)

77550-PTB-03, 114311-PZA-05, 1030-PZA-07

Name and address of DIN CERTCO Prüf- und Zertifizierungszentrum Aalen as the notified body - identification no. 0196 are to be indicated in the information brochure for the product.

**This eye-protection is to be marked on the oculars and/or the frames. The marking must include:**

Laser mode of operation	Spectral range in nm	Shade/ scale number	Identification
<b>DI4</b>			
DR	180 to 315	L7+L3	180-315 D L7 + R L3 NOIR CE
DR	>315 to 400	L4+L6	>315-400 D L4 + R L6 NOIR CE
DR	625 to 830	L4	625-830 DR L4 NOIR CE
I	625 to 670, >800 to 830	L4	625-670, >800-830 I L4 NOIR CE
I	>670 to 800	L5	>670-800 I L5 NOIR CE
DIR	>830 to 850	L3	>830-850 DIR L3 NOIR CE
DIR	>850 to 860	L2	>850-860 DIR L2 NOIR CE
DI	10600	L2	10600 DI L2 NOIR CE

### DI4 4 and 8 base

DR	180 to 315	L7+L3	180-315 D L7 + R L3 NOIR CE
DR	>315 to 395	L4+L6	>315-395 D L4 + R L6 NOIR CE
DR	625 to 830	L4	625-830 DR L4 NOIR CE
I	625 to 670, >800 to 830	L4	625-670, >800-830 I L4 NOIR CE
I	>670 to 800	L5	>670-800 I L5 NOIR CE
DIR	>830 to 850	L3	>830-850 DIR L3 NOIR CE
DIR	>850 to 860	L2	>850-860 DIR L2 NOIR CE
DI	10600	L2	10600 DI L2 NOIR CE

### Additional product specification