



EC-type examination certificate

Registration number / Reference mark C3427NOIR/R1
This certificate replaces certificate C3427NOIR.

The company

NoIR Laser Company, LLC
6155 Pontiac Trail
SOUTH LYON MI 48178
USA

Applicant's code NOIR

hereby receives the confirmation that the product/s

laser protection filter

of the type

DYE / DYE 4 and 8 base

conforms to

DIN EN 207:2002-12
Essential Requirements according to
Annex II of Directive 89/686/EEC (Edition: 1989-12)

Test report(s): 77368-PTB-02, 11433-PZA-05, 1030-PZA-07

Identification: Information see annex


See annex for further information.

DIN CERTCO GmbH
Prüf- und Zertifizierungszentrum Aalen
Gartenstraße 133, 73430 Aalen Germany



2008-09-29

Dipl.-Ing. Peter Suxdorf
Notified Body 0196



Annex

to the Certificate with Registration No. C3427NOIR/R1, dated 2008-09-29

Herewith, DIN CERTCO PZA certifies that the model is in compliance with the basic requirements of the Directive 89/686/EWG for personal protective equipment. The certificate is based both / either on the tests and / or on the technical documentation submitted by the manufacturer.

Test report(s)

77368-PTB-02, 11433-PZA-05, 1030-PZA-07

Name and address of DIN CERTCO Prüf- und Zertifizierungszentrum Aalen as the notified body - identification no. 0196 are to be indicated in the information brochure for the product.

This eye-protection is to be marked on the oculars and/or the frames. The marking must include:

Laser mode of operation	Spectral range in nm	Shade/ scale number	Identification
DYE			
D,R	180 to 315	L6+L4	180-315 D L6 + R L4 NOIR CE
D,R	>315 to 400	L4	>315-400 DR L4 NOIR CE
D,I	530 to 560	L1	530-560 DI L1 NOIR CE
D,I	>560 to 575	L2	>560-575 DI L2 NOIR CE
D,I	>575 to 600	L4	>575-600 DI L4 NOIR CE
D,I	>600 to 610	L1	>600-610 DI L1 NOIR CE
I,R	582 to 598	L6	582-598 IR L6 NOIR CE

DYE 4 and 8 base

D,R	180 to 315	L6+L4	180-315 D L6 + R L4 NOIR CE
D,R	>315 to 395	L4	>315-395 DR L4 NOIR CE
D,I	530 to 560	L1	530-560 DI L1 NOIR CE
D,I	>560 to 575	L2	>560-575 DI L2 NOIR CE
D,I	>575 to 600	L4	>575-600 DI L4 NOIR CE
D,I	>600 to 610	L1	>600-610 DI L1 NOIR CE
I,R	582 to 598	L6	582-598 IR L6 NOIR CE

Additional product specification