



## EC-type examination certificate

Registration number / Reference mark C3429NOIR/R1

This certificate replaces certificate C3429NOIR.

The company

**NoIR Laser Company, LLC**

6155 Pontiac Trail  
SOUTH LYON MI 48178  
USA

Applicant's code NOIR

hereby receives the confirmation that the product/s

**laser protection filter**

of the type

**RB2 / RB2 4 and 8 base**

conforms to

**DIN EN 207:2002-12**

**Essential Requirements according to  
Annex II of Directive 89/686/EEC (Edition: 1989-12)**

Test report(s): 77371-PTB-02, 11435-PZA-05, 1030-PZA-07

**Identification: Information see annex**

See annex for further information.

DIN CERTCO GmbH  
Prüf- und Zertifizierungszentrum Aalen  
Gartenstraße 133, 73430 Aalen



2009-09-16

U. Fallscheer  
Dipl.-Ing. Ute Fallscheer  
Notified Body 0196

## Annex

to the Certificate with Registration No. C3429NOIR/R1, dated 2009-09-16

Herewith, DIN CERTCO PZA certifies that the model is in compliance with the basic requirements of the Directive 89/686/EEG for personal protective equipment. The certificate is based both / either on the tests and / or on the technical documentation submitted by the manufacturer.

### Test report(s)

77371-PTB-02, 11435-PZA-05, 1030-PZA-07

Name and address of DIN CERTCO Prüf- und Zertifizierungszentrum Aalen as the notified body - identification no. 0196 are to be indicated in the information brochure for the product.

**This eye-protection is to be marked on the oculars and/or the frames. The marking must include:**

Laser mode of operation	Spectral range in nm	Shade/ scale number	Identification
RB2			
DR	180 to 315	L6+L4	180-315 D L6 + R L4 NOIR CE
DR	>315 to 400	L4	>315-400 DR L4 NOIR CE
DIR	>725 to 730	L1	>725-730 DIR L1 NOIR CE
DIR	>605 to 615, >715 to 725	L2	>605-615, >715-725 DIR L2 NOIR CE
DIR	>615 to 660	L3	>615-660 DIR L3 NOIR CE
DIR	>660 to 665	L4	>660-665 DIR L4 NOIR CE
DIR	>665 to 715	L4+L5+L5	>665-715 D L4 + IR L5 NOIR CE
IR	694	L7	694 IR L7 NOIR CE

### RB2 4 and 8 base

DR	180 to 315	L6+L4	180-315 D L6 + R L4 NOIR CE
DR	>315 to 400	L4	>315-400 DR L4 NOIR CE
DIR	>725 to 730	L1	>725-730 DIR L1 NOIR CE
DIR	>605 to 615, >715 to 725	L2	>605-615, >715-725 DIR L2 NOIR CE
DIR	>615 to 660	L3	>615-660 DIR L3 NOIR CE
DIR	>660 to 665	L4	>660-665 DIR L4 NOIR CE
DIR	>665 to 715	L4+L5+L5	>665-715 D L4 + IR L5 NOIR CE
IR	694	L7	694 IR L7 NOIR CE

### Additional product specification